

FULL
BODY
VITRIFIED TILES

**WE
MAKE
THE STRONG
SPARK.**

FULL
BODY
VITRIFIED TILES

Step & Riser Tiles
300X1000mm | 200X1000mm

Step & Riser Tiles

Step - 300X1000MM

Riser - 200X1000MM



MAGIC ALMOND / MATT



Step & Riser Tiles

Step - 300X1000MM

Riser - 200X1000MM




MAGIC GOLD / MATT



Step & Riser Tiles

Step - 300X1000MM

Riser - 200X1000MM



MAGIC GRAFFTY / MATT



Step & Riser Tiles

Step - 300X1000MM

Riser - 200X1000MM




MAGIC NERO / MATT



Step & Riser Tiles

Step - 300X1000MM

Riser - 200X1000MM




MAGIC PEACH / MATT



Step & Riser Tiles

Step - 300X1000MM

Riser - 200X1000MM



MAGIC SILVER / MATT



TECHNICAL SPECIFICATION

Sr. No.	CHARACTERISTICS	STANDARD AS PER ISO-13006 / EN14411 GROUP BLA	VALUE OF COMPANY	TEST METHOD
REGULATORY PROPERTIES				
01	Deviation in length & width	± 0.50%	± 0.20%	ISO-10545-2
02	Deviation in thickness	± 5.00%	± 4.00%	ISO-10545-2
03	Straightness of sides	± 0.50%	± 0.10%	ISO-10545-2
04	Rectangularity	± 0.50%	± 0.20%	ISO-10545-2
05	Surface flatness	± 0.50%	± 0.20%	ISO-10545-2
06	Colour difference	Unaltered	No Change	ISO-10545-16
STRUCTURAL PROPERTIES				
01	Water Absorption	< 0.50%	< 0.50 %	ISO-10545-3
02	Apparent density	> 2.00 g/cc	> 2.28 g/cc	DIN 51082
MASSIVE MECHANICAL PROPERTIES				
01	Modulus or rupture	Min. 35 N/mm ²	Min. 45 N/mm ²	ISO-10545-4
02	Breaking strength	Min. 1300 N	Min. 2000 N	ISO-10545-4
03	Impact resistance	As per mfg.	Min. 0.55	ISO-10545-5
SURFACE MECHANICAL PROPERTIES				
01	Deep abrasion resistance	Max. 175mm ³	Max. 132mm ³	ISO-10545-6
02	Moh's hardness	Min. 6	7	EN 101
03	Surface Abrasion Resistance	As per mfg.	N. A.	ISO-10545-7
THERMOHYDROMETRIC PROPERTIES				
01	Frost resistance	No Damage	Frost proof	ISO-10545-12
02	Thermal shock resistance	No Damage	No Damage	ISO-10545-9
03	Moisture expansion	Nil	Nil	ISO-10545-10
04	Thermal Expansion(COE)	Max. 9.0x10 ⁻⁶	Max. 6.5x10 ⁻⁶	ISO-10545-8
04	Crazing Resistance	As Per Mfg.	N.A.	ISO-10545-11
CHEMICAL PROPERTIES				
01	Chemical resistance	No Damage	No Damage	ISO-10545-13
02	Satin resistance	Resistance	Resistance	ISO-10545-14
SAFETY PROPERTIES				
01	Slip resistance (friction co efficient)	> 0.40	> 0.40	ISO-10545-17

PACKING DEATIL

SIZE	PCS./BOX	WEIGHT / BOX	AREA / BOX
200x1000mm (Riser)	3 Pcs.	15.0 Kg.	0.72 Sq. Mtr.
300x1000mm (Step)	3 Pcs.	22.5 Kg.	1.08 Sq. Mtr.

Note : Certain amount of size and shade variation is inherent in all ceramic products. Our conformity to the above fast is applicable only for quality. Colour shown are as accurate as the limitations of the printing process will allow. Prospective customers are advised to inspect a sample of the tile before ordering. Every effort has been made to ensure the accuracy of the information given. However the company reserve the right to change the specification without prior notice. Sometimes variations in shade or size being inherent to ceramic industry may occur. It is suggest to check the tiles before purchase any laying as the company does not accect responsibility once the tiles are laid.

